

Noże tokarskie składane - Toczenie wewnętrzne - System mocowania D

**DDUN 93°**



**Charakterystyka:**

Boring bar for internal turning and profiling applications equipped with rhombic negative inserts and strong cutting edges.

(angle 55°)


The dimple lock ensures good rigidity and chip flow in roughing applications.

**Zastosowanie:**

Profiling boring bar for general applications, roughing, semi-finishing and finishing.

Axial: -6°

Radial: -14°



DDUN 93°	D	h	h1	L1	L2	f	A	Rozmiar płytek	Waga	Cena
S32U DDUNR 15 prawy	32	30	15,0	350	50	22	39	DN..1506..	2,1	450,00 PLN
S32U DDUNL 15 lewy	32	30	15,0	350	50	22	39	DN..1506..	2,1	450,00 PLN
S40V DDUNR 15 prawy	40	37	18,5	400	60	27	48	DN..1506..	3,8	590,00 PLN
S40V DDUNL 15 lewy	40	37	18,5	400	60	27	48	DN..1506..	3,8	590,00 PLN

Gdańska 10  
70-660 Szczecin  
\* Telefon: +48 91 489 63 62  
\* Telefon: +48 500 189 009  
\* Fax: +48 91 462 30 00  
\* E-mail: [baltictool@baltictool.com](mailto:baltictool@baltictool.com)

12-03-2010