

Noże tokarskie składane - Toczanie wewnętrzne - System mocowania M

MDUN-K 93°




Charakterystyka:

Internal turning and profiling boring bar equipped with rhombic negative double side insert (angle 55°) with strong cutting edge. The center pin and top clamp ensure good rigidity and stability in roughing applications.

Zastosowanie:

Internal boring bar for general applications, roughing, semi-finishing and finishing.

Axial: -6°
Radial: -12°



MDUN-K 93°	D	h	h1	L1	L2	f	A	Rozmiar płytek	Waga	Cena
S25T MDUNR 15-K prawy	25	23	11,5	300	40	17	31	DN.. 1506..	0,7	260,00 PLN
S25T MDUNL 15-K lewy	25	23	11,5	300	40	17	31	DN.. 1506..	0,7	260,00 PLN
S32U MDUNR 15-K prawy	32	30	15,0	350	50	22	39	DN.. 1506..	2,1	330,00 PLN
S32U MDUNL 15-K lewy	32	30	15,0	350	50	22	39	DN.. 1506..	2,1	330,00 PLN
S40V MDUNR 15-K prawy	40	37	18,5	400	60	27	48	DN.. 1506..	3,8	440,00 PLN
S40V MDUNL 15-K lewy	40	37	18,5	400	60	27	48	DN.. 1506..	3,8	440,00 PLN

Gdańska 10
70-660 Szczecin
* Telefon: +48 91 489 63 62
* Telefon: +48 500 189 009
* Fax: +48 91 462 30 00
* E-mail: baltictool@baltictool.com

12-03-2010