

Noże tokarskie składane - Toczenie wewnętrzne - System mocowania M

MTFN 90°




Charakterystyka:

Internal turning and profiling boring bar equipped with triangular negative double side insert with strong cutting edge. The center pin and top clamp ensure good rigidity and stability in roughing applications.

Zastosowanie:

Internal boring bar for general applications, roughing, semi-finishing and finishing. Not suitable for cermet, ceramic and K10, P10 grade inserts.

Axial: -6°
Radial: -12°



MTFN 90°	D	h	h1	L1	L2	f	A	Rozmiar płytek	Waga	Cena
S25T MTFNR 16 prawy	25	23	11,5	300	40	17	34	TNM.. 1604..	0,7	260,00 PLN
S25T MTFNL 16 lewy	25	23	11,5	300	40	17	34	TNM.. 1604..	0,7	260,00 PLN
S32U MTFNR 16 prawy	32	30	15,0	350	50	22	39	TNM.. 1604..	2,1	330,00 PLN
S32U MTFNL 16 lewy	32	30	15,0	350	50	22	39	TNM.. 1604..	2,1	330,00 PLN
S40V MTFNR 16 prawy	40	37	18,5	400	60	27	48	TNM.. 1604..	3,8	440,00 PLN
S40V MTFNL 16 lewy	40	37	18,5	400	60	27	48	TNM.. 1604..	3,8	440,00 PLN

S50W MTFNR 16 prawy	50	47	23,5	450	65	35	61	TNM.. 1604..	6,5	525,00 PLN
S50W MTFNL 16 lewy	50	47	23,5	450	65	35	61	TNM.. 1604..	6,5	525,00 PLN
S40V MTFNR 22 prawy	40	37	18,5	400	60	27	48	TNM.. 2204..	3,8	440,00 PLN
S40V MTFNL 22 lewy	40	37	18,5	400	60	27	48	TNM.. 2204..	3,8	440,00 PLN
S50W MTFNR 22 prawy	50	47	23,5	450	65	35	61	TNM.. 2204..	6,5	525,00 PLN
S50W MTFNL 22 lewy	50	47	23,5	450	65	35	61	TNM.. 2204..	6,5	525,00 PLN

Gdańska 10
70-660 Szczecin
* Telefon: +48 91 489 63 62
* Telefon: +48 500 189 009
* Fax: +48 91 462 30 00
* E-mail: baltictool@baltictool.com

13-03-2010