

Noże tokarskie składane - Toczenie zewnętrzne - System mocowania M

MDJN-K 93°



Charakterystyka:

Turning and profiling toolholder equipped with rhombic negative double side insert (angle 55°) with strong cutting edge.

The center pin and top clamp ensure good rigidity and stability in roughing applications.


Zastosowanie:

External turning toolholder for general applications, roughing, semi-finishing and finishing.

Not suitable for cermet, ceramic and K10, P10 grade inserts.

For low powered machines and small pieces choose toolholder.

Axial: -6°
Radial: -7°



MDJN-K 93°	h1	b	L1	L2	f	Rozmiar płytek	Waga	Cena
MDJNR 2020 K 15-K prawy	20	20	125	34	25	DN.. 1504..	0,5	144,00 PLN
MDJNL 2020 K 15-K lewy	20	20	125	34	25	DN.. 1504..	0,5	144,00 PLN
MDJNR 2525 M 15-K prawy	25	25	150	34	32	DN.. 1504..	0,8	160,00 PLN

MDJNL 2525 M 15-K lewy	25	25	150	34	32	DN.. 1504..	0,8	160,00 PLN
MDJNR 3225 P 15-K prawy	32	25	170	34	32	DN.. 1504..	1,2	192,00 PLN
MDJNL 3225 P 15-K lewy	32	25	170	34	32	DN.. 1504..	1,2	192,00 PLN

Gdańska 10
70-660 Szczecin
* Telefon: +48 91 489 63 62
* Telefon: +48 500 189 009
* Fax: +48 91 462 30 00
* E-mail: baltictool@baltictool.com

14-03-2010