


Noże tokarskie składane - Toczanie zewnętrzne - System mocowania M

MWLN 95°




Charakterystyka:

Multipurpose toolholder equipped with trigon negative double side insert (angle 80°) with strong cutting edge. The center pin and top clamp ensure good rigidity and stability in roughing applications.

Zastosowanie:

External turning toolholder for general applications, roughing, semi-finishing and finishing. Not suitable for cermet, ceramic and K10, P10 grade inserts.

Axial: -6,5°
Radial: -6,5°



MWLN 95°	h=h1	b	L1	L2	f	Rozmiar płytek	Waga	Cena
MWLN 1616 H 06 prawy	16	16	100	15	20	WNMG.. 0604..	0,2	129,60 PLN
MWLN 1616 H 06 lewy	16	16	100	15	20	WNMG.. 0604..	0,2	129,60 PLN
MWLN 2020 K 06 prawy	20	20	125	25	25	WNMG.. 0604..	0,5	144,00 PLN
MWLN 2020 K 06 lewy	20	20	125	25	25	WNMG.. 0604..	0,5	144,00 PLN
MWLN 2525 M 06 prawy	25	25	150	25	32	WNMG.. 0604..	0,8	160,00 PLN
MWLN 2525 M 06 lewy	25	25	150	25	32	WNMG.. 0604..	0,8	160,00 PLN

Gdańska 10
70-660 Szczecin
* Telefon: +48 91 489 63 62
* Telefon: +48 500 189 009
* Fax: +48 91 462 30 00
* E-mail: baltictool@baltictool.com

14-03-2010