

Wiertła składane - 3xD

BT59..



Charakterystyka:

Helical flute indexable insert drills provide faster cutting speeds and efficient chip removal for use on conventional C.N.C. machines. This type of drills incorporates a neutral-rake geometry and screw-down spade inserts for stability and clean through-hole putting. Drills available from 9,5 to 17,5 mm.

Zastosowanie:

This drill works well on steels, alloyed steels, stainless steels and refractories.

BT59..	D	L	L2	a	d	Rozmiar płytek	Waga	Cena
BT5925.009,5	9,5-11,0	120,0	50	35	20	XPMT 095 - XPMT 110	0,2	Cena na telefon
BT5935.011,5	11,5-12,7	125,0	55	40	20	XPMT 115 - XPMT 127	0,3	Cena na telefon
BT5945.013	13,0-17,5	140,0	65	53	20	XPMT 130 - XPMT 175	0,3	Cena na telefon
BT5945.015	15,5-17,5	140,0	75	53	20	XPMT 150 - XPMT 175	0,4	Cena na telefon

Gdańska 10
70-660 Szczecin
* Telefon: +48 91 489 63 62
* Telefon: +48 500 189 009
* Fax: +48 91 462 30 00
* E-mail: baltictool@baltictool.com

05-02-2012